

GENERALS

MADE USING THE SERIES ECOFILTERS. ON THE AIR OUTLET SIDE ARE APPLIED METAL STRIPS THAT MAKE IT QUICK AND EASY THE INSTALLATION IN DRY PAINTING BOOTHS EQUIPPED WITH MAGNETIC SUPPORT.

COMPOSITION	RECYCLED KRAFT PAPER				
CONSTRUCTION	2 PERFORATED KRAFT PAPER LAYERS, PLEATED AND GLUED TO ONE EACH				
CONSTRUCTION	OTHER. METAL SKIRTS ON THE AIR OUTLET SIDE				
FRONT SIDE COLOUR	INDICATED IN THE SPECIAL SECTION				
REAR SIDE COLOUR	BROWN				
EXTENSION LIMITER	NOT AVAILABLE				
REACTION TO FIRE	BURNS				
INITIAL PRESSURE DROP (to 0,75 m/s)	30 Pa				
RECOMMENDED FINAL PRESSURE DROP	128 Pa				
MAXIMUM PRESSURE DROP	256 Pa				
ACCUMULATION CAPACITY (at 0,75 m/s)	UP TO 18 kg/m ² ⁽¹⁾				
FILTRATION EFFICIENCY	UP TO 98,1% ⁽¹⁾				
MAXIMUM OPERATING TEMPERATURE	180°C				
STRIPS SPACING	ONE EACH 26 PLEATS				
SUPPLY CONDITIONS	POLYETHYLENE BAG				

VEFIM CODE		PRICE (€)	HEIGHT (m)	LENGHT (m)	SURFACE (m²)	THICKNESS (mm)	PLEATS	No of STRIPS	FRONT SIDE COLOUR
AC23BM/1ECO/B	•	a.r.	0,90	1,00	0,90	66	26	2	WHITE
AC23BM/1,5ECO/B	٠	a.r.	0,90	1,50	1,35	66	39	3	
AC23BM/2,5ECO/B	•	a.r.	0,90	2,50	2,25	66	65	4	
AC23BM/3ECO/B	٠	a.r.	0,90	3,00	2,70	66	78	4	
AC23BM/4ECO/B	•	a.r.	0,90	4,00	3,60	66	104	5	
AC23BM/5ECO/B	•	a.r.	0,90	5,00	4,50	66	130	6	

• Material normally in stock

⁽¹⁾ Depending on the type of paint used

DIFFERENT DIMENSIONS OR VERSIONS ARE AVAILABLE ON REQUEST



Vefim S.r.l. reserves the right to update without notice the characteristics described above. This document may not be reproduced, transcribed, or translated (in part or in full) without specific written permission by Vefim S.r.l as provided for by law.





Vefim S.r.l. - Sistemi di Filtrazione www.vefim.it

Tel. +39 045.820.22.79 - Fax +39 045.827.64.95 Ufficio Vendite Italia: venditeitalia@vefim.it