

# ACRYLIC FIBRE - PHENOLIC RESIN FILTER CARTRIDGES

# CFARF



# CFARF

## GENERALS

THE FILTER CARTRIDGES SERIES CFARF PROVIDE A HIGH EFFICIENCY IN PARTICLES REMOVAL. THE LACK OF A SUPPORT CORE, PRESENT IN OTHER TYPES OF FILTER CARTRIDGES, OFFERS THE ADVANTAGE OF A GREATER RANGE OF CHEMICAL COMPATIBILITY. THEY CAN BE USED WITH INORGANIC ACIDS CONCENTRATIONS UP TO 10% AT ROOM TEMPERATURE. THEY MAY BE SMOOTH OR GROOVED: WITH THE SAME OVERALL DIMENSIONS THE CONTACT SURFACE OF THE CFARF GROOVED CARTRIDGE IS AT LEAST DOUBLE THAN THE SMOOTH ONE.

TYPE OF AREA	GROOVED OR SMOOTH
FILTERING MATERIAL	ACRYLIC FIBRE - PHENOLIC RESIN
FILTRATION RATING DEGREE ( $\mu\text{m}$ )	1 / 3 / 5 / 7 / 8 / 10 / 25 / 50 / 75 / 100
HEIGHT	10" / 20" / 30"
MAXIMUM OPERATING TEMPERATURE	120°C
RECOMMENDED PRESSURE DROP	2,4 bar
MAXIMUM PRESSURE DROP	4,8 bar
APPLICATIONS	Paint
	Solvents
	Drinking water
	Foodstuffs
	Pharmaceutical preparations
	Cosmetic products
	Industrial wastewater
	Photographic emulsions
	Dispersion of metal oxides
	Ink
Plastics	
Organic solvents	
Magnetic dispersions	

DIFFERENT DIMENSIONS OR VERSIONS ARE AVAILABLE ON REQUEST

Vefim S.r.l. reserves the right to update without notice the characteristics described above.  
This document may not be reproduced, transcribed, or translated (in part or in full) without specific written permission by Vefim S.r.l. as provided for by law.