


# FLAT METAL FILTERING CELLS VM - G2



**VM - G2**

## GENERALS

THEIR SOLID STRUCTURE AND THE FILTERING MEDIA, THAT CAN BE REGENERATED SEVERAL TIMES, MAKES THEM PARTICULARLY SUITABLE IN INDUSTRIAL PROCESSES PROVIDING HIGH LOADS OF DUST. DURING ASSEMBLY SPECIAL CARE IS GIVEN TO THE INCLUSION OF THE FILTERING PACK IN ORDER TO MAKE IT INTEGRAL WITH THE FRAME TO AVOID POSSIBLE DUST PASSAGE.

<b>FRAME</b>	<b>GALVANIZED STEEL</b>
<b>PROTECTIVE MESH</b>	<b>ON BOTH SIDES: ELECTROWELDED GALVANIZED STEEL WIRE</b>
<b>FILTERING SEPTUM</b>	<b>LAYERS OF METAL MESH IN ALUMINIUM CUSPIDATED BRAIDING</b>
<b>EFFICIENCY CLASS CEN EN 779</b>	<b>G2</b>
<b>EUROVENT CLASS</b>	<b>EU 2</b>
<b>ARRESTANCE ASHRAE 52.1.1992 Am</b>	65% (thickness 10 mm) - 70% (thickness 23 mm) - 75% (thickness 48 mm)
<b>INITIAL PRESSURE DROP</b>	5 Pa (thickness 10 mm) - 10 Pa (thickness 23 mm) - 15 Pa (thickness 48 mm)
<b>RECOMMENDED FINAL PRESSURE DROP</b>	150 Pa
<b>MAXIMUM PRESSURE DROP</b>	300 Pa
<b>MAXIMUM OPERATING TEMPERATURE</b>	200°C
<b>MAXIMUM RELATIVE HUMIDITY</b>	100%
<b>LEGEND OF DIMENSIONS</b>	
H	HEIGHT
B	BASE
T	CELL THICKNESS

Reference drawing: vefim\_celle\_piane

PRODUCT CODE	PRICE (€)	DIMENSIONS (mm)			No OF PIECES PER BOX	No OF PIECES PER PALLET	FILTERING SURFACE (m <sup>2</sup> )	AIR FLOW (Nm <sup>3</sup> /h)	FEASIBLE THICKNESS WITH EXTRA CHARGE (mm)	
		H	B	T						
VM255012	a.r.	250	500	10	20	960	0,12	700	12	a.r.
VM285912	a.r.	287	592		20	960	0,17	900	12	a.r.
VM404012	a.r.	400	400		20	720	0,16	850	12	a.r.
VM405012	a.r.	400	500		20	720	0,20	1.100	12	a.r.
VM406212	a.r.	400	625		20	540	0,25	1.350	12	a.r.
VM505012	a.r.	500	500		20	640	0,25	1.350	12	a.r.
VM506212	a.r.	500	625		20	320	0,31	1.700	12	a.r.
VM595912	a.r.	592	592		20	480	0,35	1.900	12	a.r.
VM255023	a.r.	250	500	23	20	480	0,12	700	18-20	a.r.
VM285923	a.r.	287	592		20	480	0,17	900	18-20	a.r.
VM404023	a.r.	400	400		20	600	0,16	850	18-20	a.r.
VM405023	a.r.	400	500		20	480	0,20	1.100	18-20	a.r.
VM406223	a.r.	400	625		20	360	0,25	1.350	18-20	a.r.
VM505023	a.r.	500	500		20	320	0,25	1.350	18-20	a.r.
VM506223	a.r.	500	625		20	240	0,31	1.700	18-20	a.r.
VM595923	a.r.	592	592		20	240	0,35	1.900	18-20	a.r.
VM255048	a.r.	250	500	48	10	240	0,12	700	30-35-40-45	a.r.
VM285948	a.r.	287	592		10	240	0,17	900	30-35-40-45	a.r.
VM404048	a.r.	400	400		10	300	0,16	850	30-35-40-45	a.r.
VM405048	a.r.	400	500		10	240	0,20	1.100	30-35-40-45	a.r.
VM406248	a.r.	400	625		10	180	0,25	1.350	30-35-40-45	a.r.
VM505048	a.r.	500	500		10	160	0,25	1.350	30-35-40-45	a.r.
VM506248	a.r.	500	625		10	120	0,31	1.700	30-35-40-45	a.r.
VM595948	a.r.	592	592		10	120	0,35	1.900	30-35-40-45	a.r.

• Material normally in stock

DIFFERENT DIMENSIONS OR VERSIONS ARE AVAILABLE ON REQUEST

Vefim S.r.l. reserves the right to update without notice the characteristics described above.  
This document may not be reproduced, transcribed, or translated (in part or in full) without specific written permission by Vefim S.r.l. as provided for by law.



Vefim S.r.l. - Sistemi di Filtrazione  
[www.vefim.it](http://www.vefim.it)  
Tel. +39 045.820.22.79 - Fax +39 045.827.64.95  
Ufficio Vendite Italia: [venditeitalia@vefim.it](mailto:venditeitalia@vefim.it)