

CELLS WITH CARDBOARD FRAME
PUNCHED WITH FIBRE-GLASS

AC - G3



AC - G3

GENERALS

FILTERING CELLS TO MISS IN CARDBOARD FULLY STAMPED A MICROWAVE FORMING ONE STRONG FRAME.

FRAME	CARTONE E/KBMT/242
PROTECTIVE MESH	CARTONE E/KBMT/242
FILTERING SEPTUM	LONG GLASS FIBRE
EFFICIENCY CLASS CEN EN 779	G3
EUROVENT CLASS	EU 3
ARRESTANCE ASHRAE 52.1.1992 Am	85%
INITIAL PRESSURE DROP	15 Pa
RECOMMENDED FINAL PRESSURE DROP	250 Pa
MAXIMUM OPERATING TEMPERATURE	120°C
MAXIMUM RELATIVE HUMIDITY	100%
<p>LEGEND OF DIMENSIONS</p> <p>H HEIGHT B BASE T CELL THICKNESS</p>	

Reference drawing: vefim_celle_cartone

PRODUCT CODE	PRICE (€)	DIMENSIONS (mm)			No OF PIECES FOR BOX	FILTERING SURFACE (m ²)	AIR FLOW (Nm ³ /h)
		H	B	T			
AC99N	a.r.	170	380	23	80	0,07	400
AC113	a.r.	200	380		80	0,08	400
AC112N	a.r.	380	380		80	0,14	800
AC103	a.r.	287	592	48	16	0,17	900
AC76	a.r.	400	500		20	0,20	1.100
AC45	a.r.	400	625		20	0,25	1.300
AC48	a.r.	490	660		20	0,32	1.700
AC11	a.r.	500	500		20	0,25	1.300
AC18	a.r.	500	600		20	0,30	1.600
AC91	a.r.	500	625		20	0,31	1.700
AC36	a.r.	500	660		20	0,33	1.800
AC105N	a.r.	500	860		10	0,43	2.300
AC101N	a.r.	592	592		8	0,35	1.900

• Material normally in stock

DIFFERENT DIMENSIONS OR VERSIONS ARE AVAILABLE ON REQUEST

Vefim S.r.l. reserves the right to update without notice the characteristics described above.
This document may not be reproduced, transcribed, or translated (in part or in full) without specific written permission by Vefim S.r.l as provided for by law.