

**CELLS WITH CARDBOARD FRAME
MIXED PUNCHED
AC - G4**



AC - G4

GENERALS

FILTERING CELLS TO MISS IN CARDBOARD FULLY STAMPED A MICROWAVE FORMING ONE STRONG FRAME.

FRAME	CARTONE E/KBMT/242
PROTECTIVE MESH	CARTONE E/KBMT/242
FILTERING SEPTUM	WHITE POLYESTER PRE-FILTER + LONG FIBRE GLASS
EFFICIENCY CLASS CEN EN 779	G4
EUROVENT CLASS	EU 4
ARRESTANCE ASHRAE 52.1.1992 Am	90%
INITIAL PRESSURE DROP	39 Pa
RECOMMENDED FINAL PRESSURE DROP	250 Pa
MAXIMUM OPERATING TEMPERATURE	120°C
MAXIMUM RELATIVE HUMIDITY	100%
LEGEND OF DIMENSIONS	
H	HEIGHT
B	BASE
T	CELL THICKNESS

Reference drawing: vefim_celle_cartone

PRODUCT CODE	PRICE (€)	DIMENSIONS (mm)			No OF PIECES FOR BOX	FILTERING SURFACE (m ²)	AIR FLOW (Nm ³ /h)
		H	B	T			
AC102N	a.r.	592	592	48	8	0,35	1.900
AC106N	a.r.	500	860		10	0,43	2.300
AC12	a.r.	500	500		20	0,25	1.300
AC19	a.r.	500	600		20	0,30	1.600
AC37	a.r.	500	660		20	0,33	1.800
AC46	a.r.	400	625		20	0,25	1.300
AC49	a.r.	490	660		20	0,32	1.700
AC77	a.r.	400	500		20	0,20	1.100
AC92	a.r.	500	625		20	0,31	1.700
AC104	a.r.	287	592		16	0,17	900

• Material normally in stock

DIFFERENT DIMENSIONS OR VERSIONS ARE AVAILABLE ON REQUEST

Vefim S.r.l. reserves the right to update without notice the characteristics described above.
This document may not be reproduced, transcribed, or translated (in part or in full) without specific written permission by Vefim S.r.l as provided for by law.



Vefim S.r.l. - Sistemi di Filtrazione
www.vefim.it
Tel. +39 045.820.22.79 - Fax +39 045.827.64.95
Ufficio Vendite Italia: venditeitalia@vefim.it