

CARTRIDGE FILTERS WITH ACTIVE CARBONS

ACCART



ACCART

GENERALS

THE CARTRIDGE FILTERS WITH ACTIVE CARBONS (ACCART SERIES) ARE CONTAINERS CONSISTING OF A STURDY STRUCTURE WITHIN WHICH ARE THE ACTIVE CARBONS. THEY ARE WIDELY USED IN PAINT SYSTEMS, BUT CAN ALSO BE USED FOR OTHER APPLICATIONS.

TYPE OF CARBON	AIRASSORB AC22/25 ⁽¹⁾
RECHARGEABLE	YES
CONTAINMENT STRUCTURE	GALVANIZED STEEL METAL SHEET
BOTTOMS	SHOCK AND HEAT-RESISTANT ABS ⁽²⁾
MAXIMUM OPERATING RELATIVE HUMIDITY	70%
MAXIMUM OPERATING TEMPERATURE	40°
LEGEND OF DIMENSIONS H HEIGHT DE CARTRIDGE OUTER DIAMETER ϕ DI CARTRIDGE INTERNAL DIAMETER ϕ	

Reference drawing: vefim_accart_cil

PRODUCT CODE	PRICE (€)	CONTENTS (kg ca.)	DIMENSIONS (mm)			FILTERING SURFACE (m ²)	BED THICKNESS (mm)	AIR SPEED			PRESSURE DROP (Pa)	CONTACT TIME (s)
			DE	DI	H			(m/s)	(m ³ /h)			
AC29	● a.r.	20 kg	350	275	1000	0,98	38	0,05	177	22	0,75	
								0,10	353	35	0,38	
								0,25	883	120	0,15	

COMPATIBILITY: SAIMA - TERMOMECCANICA FB - TERMOMECCANICA GL - USI ITALIA

AC29/7	a.r.	27 kg	370	255	1000	0,98	58	0,05	177	25	1,15
								0,10	353	37	0,58
								0,25	883	125	0,23

COMPATIBILITY: BLOWTHERM

AC29/10	a.r.	17,5 kg	320	240	1000	0,88	40	0,05	158	18	0,80
								0,10	317	33	0,40
								0,25	791	116	0,16

COMPATIBILITY: NOVA VERTA

● Material normally in stock

⁽¹⁾ As per the data sheet AC22/25

⁽²⁾ Availability to provide galvanized steel beds

DIFFERENT DIMENSIONS OR VERSIONS ARE AVAILABLE ON REQUEST
OTHER TYPES OF ACTIVE CARBONS ARE AVAILABLE ON REQUEST

Vefim S.r.l. reserves the right to update without notice the characteristics described above.
This document may not be reproduced, transcribed, or translated (in part or in full) without specific written permission by Vefim S.r.l as provided for by law.

CARTRIDGE FILTERS FOR ACTIVE CARBONS

ACCART



ACCART

GENERALS

THE CARTRIDGE FILTERS WITH ACTIVE CARBONS (ACCART SERIES) ARE CONTAINERS CONSISTING OF A STURDY STRUCTURE WITHIN WHICH ARE THE ACTIVE CARBONS. THEY ARE WIDELY USED IN PAINT SYSTEMS, BUT CAN ALSO BE USED FOR OTHER APPLICATIONS.

RECHARGEABLE		YES
CONTAINMENT STRUCTURE		GALVANIZED STEEL METAL SHEET
BOTTOMS		SHOCK AND HEAT-RESISTANT ABS ⁽¹⁾
<p>LEGEND OF DIMENSIONS</p> <p>H HEIGHT</p> <p>DE CARTRIDGE OUTER DIAMETER ϕ</p> <p>DI CARTRIDGE INTERNAL DIAMETER ϕ</p>		

Reference drawing: vefim_accart_cil

PRODUCT CODE	PRICE (€)	SUPPLY CONDITIONS	DIMENSIONS (mm)			COMPATIBILITY	CONTENT (approx. kg)
			DE	DI	H		
AC20	a.r.	EMPTY	350	275	1000	SAIMA - TERMOMECCANICA FB TERMOMECCANICA GL - USI	20
AC20/7	a.r.		370	255	1000	BLOWTHERM	27
AC20/10	a.r.		320	240	1000	NOVA VERTA	17,5

• Material normally in stock

⁽¹⁾ Availability to provide galvanized steel beds

DIFFERENT DIMENSIONS OR VERSIONS ARE AVAILABLE ON REQUEST
OTHER TYPES OF ACTIVE CARBONS ARE AVAILABLE ON REQUEST

Vefim S.r.l. reserves the right to update without notice the characteristics described above.
This document may not be reproduced, transcribed, or translated (in part or in full) without specific written permission by Vefim S.r.l. as provided for by law.



Vefim S.r.l. - Sistemi di Filtrazione
www.vefim.it
 Tel. +39 045.820.22.79 - Fax +39 045.827.64.95
 Ufficio Vendite Italia: venditeitalia@vefim.it